

# ITF COURT PACE CLASSIFICATION PROGRAMME

## TECHNICAL DATA SHEET

|                     |                                           |                |                                                          |
|---------------------|-------------------------------------------|----------------|----------------------------------------------------------|
| <b>Brand name</b>   | Plexipave                                 |                |                                                          |
| <b>Company Name</b> | California Products Corp.                 |                |                                                          |
| <b>Address</b>      | 150 Dascomb Road<br>Andover, MA 01810 USA |                |                                                          |
| <b>Telephone</b>    | 978-623-9980                              | <b>Fax</b>     | 978-623-9960                                             |
| <b>Email</b>        | info@plexipave.com                        | <b>Website</b> | <a href="http://www.plexipave.com">www.plexipave.com</a> |
|                     |                                           |                |                                                          |

### TECHNICAL DATA

#### GENERAL DESCRIPTION:

The Plexipave Color Surfacing System, developed through almost four decades of technological advancements in acrylic athletic surfacing, is a durable, asbestos free, colorful playing surface compatible with hot mix asphalt and suitably prepared concrete. The Plexipave System is a combination of texture coats and finish coats that provide a long-wearing color surface of uniform texture. The system is suitable for all climatic conditions and protects asphalt from ultraviolet ray deterioration. Based on 100% acrylic water vehicle coatings, the Plexipave Color Surfacing System dries rapidly and allows surfaces to breathe enabling moisture vapor to pass through the dried film.

#### SPECIFICATION OF COURT SURFACE MATERIALS AND CONSTRUCTION, INCLUDING METHOD OF APPLICATION:

##### STANDARD ASPHALT INSTALLATION

New Construction

- Level with Court Patch binder mix or Plexipatch
- 1 coat Acrylic Resurfacer
- 3 coats Color Base/Plexichrome mix @ 0.15 gals sq. yd

##### STANDARD CONCRETE INSTALLATION

New Construction

- Acid Etch with Concrete Preparer.
- Level with Court Patch Binder.
- Ti-Coat as Primer.
- 1 Coat Acrylic Resurfacer.
- 3 coats Color Base/Plexichrome mix @ 0.15 gals sq. yd

**LINE MARKINGS:**

Apply one coat of 100% Acrylic Plexicolor Line Paint with a roller, Brush or airless sprayer.

**MAINTENANCE GUIDELINES:**

Keep courts free of dirt or debris, wash with water monthly.

**WARRANTY:**

Extended warranties are available when surface is installed by an Authorized Applicator of the Plexipave System. Materials are covered by a limited manufacturer's warranty.

*Disclaimer. The ITF cannot be held responsible for, and accepts no liability for, the failure of any product or service manufactured, produced or provided according to the information given in this data sheet or for any acts or omissions made in reliance upon it or in connection with it.*